

Configure Nginx webserver on Jump server / Bastion host

155 admin October 5, 2024 [Tweaks & Configuration](#) 30056

How to install [Nginx](#) on the Ezeelogin SSH jump server?

Overview: This article describes how to install and configure Nginx with PHP-FPM on both Debian 9 and CentOS, tailored for an Ezeelogin SSH jump server setup.

To set up Nginx on your Ezeelogin SSH jump server, follow these step-by-step instructions tailored for both **Debian 9** and **CentOS** environments:

1. Installing Nginx and PHP-FPM on Debian 9:

Step 1(A): Update Packages and Install [Nginx](#) with PHP-FPM:

```
root@gateway:~# apt update ; apt-get install nginx php-fpm
```

Step 1(B): Configure Default Nginx Server Block. Open the default configuration file:

```
root@gateway:~# vi
```

Step 1(C): We need to make some changes to this file for our site.

The changes that you need to make are in red in the text below. If you prefer, you may just copy and paste everything, then replace the value of `server_name` & `root` (Document root) with the appropriate domain name or IP address & Document root:

```
# Default server configuration

server {

    listen 80 default_server;

    listen [::]:80 default_server;

    # SSL configuration

    # listen 443 ssl default_server;

    # listen [::]:443 ssl default_server;

    root /var/www/html;

    index index.php

    server_name (Add your hostname or IP);

    location / {

        # First attempt to serve request as file, then

        # as directory, then fall back to displaying a 404.

        try_files $uri $uri/ =404;

    }

    # pass PHP scripts to FastCGI server

    location ~ .php$ {

        include snippets/fastcgi-php.conf;
```

```
fastcgi_pass unix:/var/run/php/php7.0-fpm.sock;

}

if (!-f $request_filename) {

rewrite ^/(.*)$/ezlogin/index.php?$1 last;

}

# deny access to .htaccess files, if Apache's document root

# concurs with nginx's one

#location ~ /\.ht {

# deny all;

#}

}
```

Step 1(D): After making the changes, save and close the file.

Step 1(E): Restart Nginx and PHP-FPM Services to make the necessary changes:

```
root@gateway:~# systemctl reload nginx.service

root@gateway:~# systemctl reload php7.0-fpm.service
```

Step 1(F): Make sure to install the [loncube Loader](#)

2. Install & Configure [Nginx](#) on Centos:

Step 2(A): Install Nginx and PHP-FPM:

```
root@gateway:~# yum install epel-release ; yum install nginx
```

Step 2(B): Install & configure php handler

```
root@gateway:~# yum install php-fpm
```

Step 2(C): Open the main php-fpm configuration file with root privileges, search for "**cgi.fix_pathinfo=1**" and set it to "**cgi.fix_pathinfo=0**"

```
root@gateway:~# vi /etc/php.ini
```

Step 2(D): Set "**cgi.fix_pathinfo=0**". Save and close the file when you are finished.

```
cgi.fix_pathinfo=0
```

Step 2(E): Open the php-fpm pool configuration file `www.conf` using the editor.


```
root@gateway:~# vi /etc/php-fpm.d/www.conf
```




Step 2(F): Find the line that specifies the **listen parameter**, and change it so it looks like the following:



Step 2(G): Next, find the lines that set the **listen.owner** and **listen.group** and **uncomment** them. They should look like this:




Step 2(H): Lastly, find the lines that set the **user** and **group** and change their values from "**Apache**" to "[nginx](#)":



Step 2(I): After making changes save and quit.

Step 2(J): Start the PHP processor by running the following commands:



```
root@gateway:~# sudo systemctl enable php-fpm
```

```
root@gateway:~# sudo systemctl restart nginx
```

```
root@gateway:~# sudo systemctl restart php-fpm
```

3. Configure [Nginx](#) to Process PHP Pages:

Step 3(A): Open the default [Nginx](#) server block configuration file by opening the default configuration file:

```
root@gateway:~# vi /etc/nginx/conf.d/default.conf
```

Step 3(B): We need to make some changes to this file for our site.

The changes that you need to make are in red in the text below. If you prefer, you may just copy and paste everything, then replace the value of server_name & root (Document root) with the appropriate domain name or IP address & Document root:

```
server_name server_domain_name_or_IP;
```

```
root /var/www/html;  
    index.php
```

```
try_files $uri $uri/ =404;
```

```
root /var/www/html;
```

```
location ~ .php$ {  
    try_files $uri =404;  
    fastcgi_pass unix:/var/run/php-fpm/php-fpm.sock;  
    fastcgi_index index.php;  
    fastcgi_param SCRIPT_FILENAME $document_root$fastcgi_script_name;  
    include fastcgi_params;  
}  
  
if (!-f $request_filename) { rewrite ^/(.*)$ /ezlogin/index.php?$1 last;  
}
```

Step 3(C): After making changes save and close the file.

Step 3(D): Restart Nginx to make the necessary changes:

```
root@gateway:~# systemctl restart nginx
```

If you have any difficulties contact [support](#).

Related Articles:

[502 error on login with nginx.](#)

[404 error on login with nginx.](#)

Online URL:

<https://www.ezeelogin.com/kb/article/configure-nginx-webserver-on-jump-server-bastion-host-155.html>