configure jump server to use SSL for MySQL

206 Manu Chacko October 11, 2024 Tweaks & Configuration 13645

How to configure Ezeelogin jump server to use SSL for MySQL database connections on centos?

Overview: This article explains configuring SSL for MySQL on the Ezeelogin jump server using CentOS 7 and MySQL 5.5. It includes checking SSL status, generating certificates, updating MySQL and Ezeelogin configurations, and verifying the connection to ensure secure database access.

Mysql-SSL setup on Centos 7,Mysql server 5.5 version

Step 1. Check the Current SSL/TLS Status

Log into a MySQL session

```
root@gateway:~# mysql -u root -p -h 127.0.0.1
```

Show the state of the SSL/TLS variables by typing:

```
mysql> SHOW VARIABLES LIKE '%ssl%';

Output
+---------------+----------+
| Variable_name | Value    |
+---------------+----------+
| have_openssl  | DISABLED |
| have_ssl      | DISABLED |
| ssl_ca        |          |
| ssl_capath    |          |
| ssl_cert      |          |
| ssl_cipher    |          |
| ssl_crl       |          |
| ssl_crlpath   |          |
| ssl_key       |          |
+---------------+----------+
9 rows in set (0.01 sec)
```

The **have_openssl** and **have_ssl variables** are both marked as DISABLED. This means that SSL functionality has been compiled into the server, but that it is not yet enabled.

Step 2. Generate SSL/TLS Certificates and Keys

Create a clean environment

```
root@gateway:~# mkdir /etc/certs && cd /etc/certs
```

Create the CA certificate

```
root@gateway:~# openssl genrsa 2048 > ca-key.pem
```

```
root@gateway:~# openssl req -new -x509 -nodes -days 3600 \
-key ca-key.pem -out ca.pem
```

Create the server certificate, remove passphrase, and sign it

```
root@gateway:~# openssl req -newkey rsa:2048 -days 3600 \
-nodes -keyout server-key.pem -out server-req.pem


root@gateway:~# openssl rsa -in server-key.pem -out server-key.pem

root@gateway:~# openssl x509 -req -in server-req.pem -days 3600 \
-CA ca.pem -CAkey ca-key.pem -set_serial 01 -out server-cert.pem
```

Create the client certificate, remove passphrase, and sign it

```
root@gateway:~# openssl req -newkey rsa:2048 -days 3600 \
-nodes -keyout client-key.pem -out client-req.pem

root@gateway:~# openssl rsa -in client-key.pem -out client-key.pem

root@gateway:~# openssl x509 -req -in client-req.pem -days 3600 \
-CA ca.pem -CAkey ca-key.pem -set_serial 01 -out client-cert.pem
```

After generating the certificates, verify them:

```
root@gateway:~# openssl verify -CAfile ca.pem server-cert.pem client-cert.pem


output

server-cert.pem: OK
client-cert.pem: Ok
```

Enable SSL for MySQL

We have to edit the MySQL configuration file **'/etc/my.cnf'**

In the '**[mysqld]**' section, paste the configuration below.

```
root@gateway:~# vi /etc/my.cnf

ssl-ca=/etc/certs/ca.pem

ssl-cert=/etc/certs/server-cert.pem

ssl-key=/etc/certs/server-key.pem
```

Restart the MySQL service

```
root@gateway:~# systemctl restart mysql
```

After restarting, open up a new MySQL session using the same command as before.

```
root@gateway:~# mysql -u root -p -h 127.0.0.1
```

Check state of the SSL/TLS variables by typing:

```
mysql> SHOW VARIABLES LIKE '%ssl%';

Output
+---------------+----------------+
| Variable_name | Value          |
+---------------+----------------+
| have_openssl  | YES            |
| have_ssl      | YES            |
| ssl_ca        | Ca.pem         |
| ssl_capath    |                |
| ssl_cert      | server-cert.pem|
| ssl_cipher    |                |
| ssl_crl       |                |
| ssl_crlpath   |                |
| ssl_key       | server-key.pem |
+---------------+----------------+
9 rows in set (0.01 sec)
```

The **have_openssl** and **have_ssl** variables read **"YES"** instead of "**DISABLED**" this time.

Check the connection details by the following command :

```
root@gateway:~# mysql -u ezlogin_database_username -p -h hostname or ip --ssl-ca=/etc/certs/ca.pem --ssl-cert=/etc/certs/client-cert.pem --ssl-key=/etc/certs/client-key.pem

example :


root@gateway:~# mysql -u ezlogin_xxxx -p -h 10.11.1.11 --ssl-ca=/etc/certs/ca.pem --ssl-cert=/etc/certs/client-cert.pem --ssl-key=/etc/certs/client-key.pem
```

In Case the certificate verification has been failed, refer **SSL certificate failed with MYSQL SSL**

```
mysql> \s

---------------

. . .

SSL: Cipher in use is DHE-RSA-AES256-SHA

. . .

Connection: 127.0.0.1 via TCP/IP

. . .

----------------
```

SSL cipher is displayed, indicating that SSL is being used to secure our connection.

Step 3. Configure ezeelogin jump server to use SSL for Mysql 5.5

Add mysql_ssl_key,mysql_ssl_cert,mysql_ssl_ca to **/usr/local/etc/ezlogin/ez.conf**

Edit the **/usr/local/etc/ezlogin/ez.conf** file add the following

```
root@gateway:~# vi /usr/local/etc/ezlogin/ez.conf

#Add the following
system_folder /var/www/ezlogin/
force_https no
uri_path /ezlogin/
db_host 10.10.1.11
db_port 3306
db_name ezlogin_qzms
db_user ezlogin_edcjwz
db_pass dsH)$s5xAE[QgFms
db_prefix aqvo_
cookie_encryption_key ASvs8^pnu^^X9
cookie_name lcrrfs
cookie_path /ezlogin/
www_folder /var/www/html/ezlogin/
admin_user admin
mysql_encrypt yes
mysql_ssl_key /etc/certs/client-key.pem
mysql_ssl_cert /etc/certs/client-cert.pem
mysql_ssl_ca /etc/certs/ca.pem
mysql_ssl_capath /etc/certs/
mysql_ssl_verify no
```

Note: Make sure that you have changed db_port to 3306 & db_host to IP Address of your host

Step 4. Change the bind address & allow the Ezeelogin jump server user to access the database.

Edit the /etc/mysql/mysql.conf.d/mysqld.cnf & change bind-address

```
root@gateway:~# vi /etc/mysql/mysql.conf.d/mysqld.cnf

Change bind-address to host ip(server ip)

bind-address x.x.x.x (Host ip)
```

Restart the MySQL service

```
root@gateway:~# systemctl restart mariadb
```

you can find out Ezeelogin jump server **dbname** and Ezeelogin Mysql **username** from the **ez.conf** file

```
root@gateway:~# cat /usr/local/etc/ezlogin/ez.conf

system_folder /var/www/ezlogin/
force_https no
uri_path /ezlogin/
db_host 10.10.1.11
db_port 3306
db_name ezlogin_qzms
```

db_user ezlogin_edcjwz
db_pass dsH)$s5xAE[QgFms
db_prefix aqvo_
cookie_encryption_key ASvs8^pnu^^X9
cookie_name lcrrfs
cookie_path /ezlogin/
www_folder /var/www/html/ezlogin/
admin_user admin
mysql_encrypt yes
mysql_ssl_key /etc/certs/client-key.pem
mysql_ssl_cert /etc/certs/client-cert.pem
mysql_ssl_ca /etc/certs/ca.pem
mysql_ssl_capath /etc/certs/
mysql_ssl_verify no

Login to mysql

root@gateway:~# mysql -u root -p

[Enter password]

mysql> grant all on ezlogin_databasename.* to 'mysql_username'@'%' identified by 'password';

example : mysql > grant all on ezlogin_xxx.* to 'ezlogin_xxxx'@'%' identified by 'dsH)$s5xAE[QgFmfsfgg';

mysql > flush privileges;

mysql > exit

Check if you can log in to MySQL using Ezeelogin databases

root@gateway:~# mysql -u ezeelogin_databasename_username -h 10.11.1.11 -p

Enter Password:

mysql >

mysql > exit

Note: If you have any difficulties please **contact support**

Related Articles:

Configure Ezeelogin to use SSL for MySQL version 8 on Ubuntu

Configure ssh jump server to use SSL for Mariadb

Increase script execution time in Ubuntu and CentOS

configure jump server to use SSL for MySQL server 5.7 version

Basic MySQL commands for troubleshooting database related issues in Ezeelogin

Unable to access GUI while using MySQL SSL

failed to connect to database: Error: TLS/SSL error: Permission denied

Online URL: https://www.ezeelogin.com/kb/article/configure-jump-server-to-use-ssl-for-mysql-206.html