How To Create a Self-Signed SSL Certificate for Nginx on debian

217 Manu Chacko July 16, 2024 Tweaks & Configuration 6034

How to Create an SSL Certificate on SSH jump server for Nginx on Debian

Overview: This article describes how to create a self-signed SSL certificate, configure Nginx to use SSL, and adjust the Nginx configuration to enable SSL for secure web server communication.

1. Create a Self-signed Certificate

When we request a new certificate, we can specify how long the certificate should remain valid by changing the 365 to the number of days we prefer. As it stands this certificate will expire after one year.

```
:~# sudo openssl req -x509 -nodes -days 365 -newkey rsa:2048 -keyout /etc/ssl/private/nginx-selfsigned.key -out /etc/ssl/certs/nginx-selfsigned.crt
```

With this command, we will be both creating the self-signed SSL certificate and the server key. This command will prompt the terminal to display a list of fields that need to be filled in. Fill out the prompts appropriately. The most important line is the one that requests the Common Name (ex. server FQDN or YOUR name). You need to enter the domain name associated with your server or, more likely, your server's public IP address.

```
Output:

Country Name (2 letter code) [AU]:US

State or Province Name (full name) [Some-State]:New York

Locality Name (eg, city) []:New York City

Organization Name (eg, company) [Internet Widgits Pty Ltd]:Bouncy Castles, Inc.
```

```
Organizational Unit Name (eg, section) []:Ministry of Water Slides

Common Name (e.g. server FQDN or YOUR name) []:server_IP_address

Email Address []:admin@your_domain.com

Professible fine in created will be placed in the appropriate subdirectories of the complex shippers disectory. Figuration shipper in the complex shippers disectory. Figuration shipper in the complex shippers disectory. Figuration shipper in the complex shippers are the complex shippers as a complex shipper in the complex shippers are the complex shippers as a complex shipper in the complex shippers are the complex shippers as a complex shippers are the complex shippers and complex shippers are the complex shippers are the complex shippers and complex shippers are the complex shippers and complex shippers are the complex shippers and complex shippers are the complex shippers are the complex shippers and complex shippers are the complex shippers and complex shippers are the complex shippers and complex s
```

ssl_certificate /etc/ssl/certs/nginx-selfsigned.crt;
ssl_certificate_key /etc/ssl/private/nginx-selfsigned.key;
When vou've added those lines save and close the file_
Before we'go any further; let's back up our current server block file:
:~# sudo cp /etc/nginx/sites-available/default /etc/nginx/sites-available/default.bak

Open the server block file to make adjustments.

```
root@jumpserver:~# sudo nano /etc/nginx/sites-available/default
server {
listen 80 default_server;
listen [::]:80 default_server;
server_name server_domain_or_IP;
return 302 https://$server_name$request_uri;
}
server {
```

```
# SSL configuration
listen 443 ssl default_server;
listen [::]:443 ssl default_server;
include snippets/self-signed.conf;
. . .
```

Your virtual host is now all setup! Save and Exit Restart Apache.

root@jumpserver:~# sudo systemctl restart nginx

Related Articles:

Configure the Jump server to use SSL for Mysql.

Install SSL cert in Jump Server.

Install Master/Slave with Mysql ssl.

Online URL:

https://www.ezeelogin.com/kb/article/how-to-create-a-self-signed-ssl-certificate-for-nginx-on-debian-217.html