

How to reset cluster keys in ezeelogin Master-slave Configuration ?

219 Manu Chacko April 4, 2024 [Tweaks & Configuration](#) 3733

How to reset the cluster key in order to use the RSA key?

Regenerate cluster key

You need to reinstall the secondary/slave (cluster) node after resetting the cluster key

1. Enter the following command to reset the cluster key on Primary(master) Ezeelogin.

```
root@jumpserver:~# /usr/local/ezlogin/eztool.php  
-regenerate_cluster_key
```

This will change the DSA key to RSA as well.

The cluster key is located at /usr/local/etc/ezlogin/id_clkey

2. Uninstall on ezeelogin on secondary /slave.

Enter the following command to Uninstall Ezeelogin

```
root@jumpserver:~# /usr/local/sbin/uninstall_ezlogin.php
```

3. Install ezeelogin secondary /slave node

Execute the following command

```
root@jumpserver:~# sh ezlogin_7.x.x.bin -- -secondary -othernode  
<ip_address of master node>
```

Refer to this article to install the Secondary/slave node

[Install slave / secondary node for high availability in the jump server](#)

Online URL:

<https://www.ezeelogin.com/kb/article/how-to-reset-cluster-keys-in-ezeelogin-master-slave-configuration-219.html>