

Migrate jump server installation from one server to another

31 admin June 14, 2024 [Migration & Maintenance](#) 8630

How to move the Ezeelogin bastion host from one server to another(MIGRATION)?

Synopsis: This article offers a step-by-step guide on how to migrate an Ezeelogin jump server from one server to another.

1. How to migrate Ezeelogin installation from one server to another?

Step 1.a: If you are using the **Ezeelogin** master-slave configuration, you should verify and confirm **database** is in **sync**. Refer below article to verify database connectivity.

<https://www.ezeelogin.com/kb/article/error-this-node-in-cluster-has-local-changes-please-verify-database-and-synchronize-db-sync-incomplete-361.html>

Step 1.b: Run the script **/usr/local/sbin/backup_ezlogin.php** on the current server to create the backup archive.

The backup archive would be created in **/var/ezlogin.xx.bin**

The contents in users home directories will not be backed up automatically. You will need to manually transfer the contents, including the keys, to the new primary server.

The directory **/var/log/ezlogin** stores the user ssh sessions that are recorded. This directory could run into huge size (1GB >) which would cause the backup script to take long to complete (The log directory has to be tar'ed and then gzip'ed compressed which is time-consuming and resource intensive). In such, cases its advisable to skip the log directory while running the backup script as follows.

```
[root@jumpserver ~]# /usr/local/sbin/backup_ezlogin.php -nologs
```

After restoring a backup, you would need to **copy** or **rsync** **/var/log/ezlogin** directory to the new server.

```
root@old_primary_server ~]# rsync -rt /var/log/ezlogin/* root@new_primary_ip:/var/log/ezlogin/
```

Step 1.c: Make sure that Ezeelogin licensed **IP** is changed to **new IP** from the [customer portal](#).

If you are using an owned license, then you can skip this step.

Step 1.d: Make sure that the new server has the **same** versions of **PHP** and **MySQL** server, and also install the webserver, **PHP** modules, and [ioncube](#). Refer to below article to install it in different OS.

<https://www.ezeelogin.com/kb/article/setup-and-configure-ssh-jump-server-2.html>

Step 1.e: Move the **executable ezlogin.xx.bin** archive to the **new server**, and execute the **.bin** file.

Follow the on-screen instructions and confirm everything is working in the new server such as (login to GUI, Ezsh shell, remote server, etc.)

In case of any error, while restoring **check the restore log**. Refer to the below step to find the log.

```
root@new_primary_server ~]# tail /var/log/ezlogin_restore.log
```

Refer to the below article **to fix the PHP limit error** while restoring.

<https://www.ezeelogin.com/kb/article/backup-restore-crashes-abruptly-without-any-error-328.html>

2. How to restore slave/secondary installation?

We **don't** need to **migrate** and **restore** the **slave/secondary** node, as the master and slave nodes are **identical**. We can **install** a **slave** node identical to the master node. Refer below article to install the slave node.

<https://www.ezeelogin.com/kb/article/install-slave-secondary-node-for-high-availability-in-jump-server-21.html>

3. How to restore logs from the old slave server to the new slave server?

You can use the following steps to restore logs in primary when you skip the log directory from backup.

Step 3.a: Copy logs from old slave server to new slave. Run the below command on the **old slave server**.

```
root@old_slave_server ~]# rsync -rt /var/log/ezlogin/*  
root@new_slave_ip:/var/log/ezlogin
```

Step 3.b: Run the below script on the new slave server to **repopulate** SSH logs.

```
root@new_slave_server ~]# /usr/local/ezlogin/eztool.php  
-reimport_logs
```

Step 3.c: Click on the view icon on the new slave **Ezeelogin SSH log** from GUI to confirm log files have been copied and repopulated. Refer below screenshot.

The screenshot shows the Ezeelogin web interface. The left sidebar contains a menu with 'Users' highlighted in green. The main content area has a search filter for 'SSH Log' and a table of logs. A green arrow points to the 'Actions' column of the table.

Search

User: -- All --

Server: -- All --

Log Type: -- All --

From: 2022-06-22 16:18 10

To: 2022-06-24 16:18 10

Rows Per Page: 10

Note: Logs are local to the node. Search the other node as well if cluster is configured.

Reset Find

SSH logs

<input type="checkbox"/>	User	SSH User	Server	Log Type	Status	Encryption	Time ↑	mExec ID	Actions
<input type="checkbox"/>	+ ezadmin	root	centos server	input	Ended	0	2022-06-23 19:44:09		
<input type="checkbox"/>	+ ezadmin	root	centos server	output	Ended	0	2022-06-23 19:44:09		
<input type="checkbox"/>	+ ezadmin	root	centos server	input	Ended	0	2022-06-23 19:43:57		
<input type="checkbox"/>	+ ezadmin	root	centos server	output	Ended	0	2022-06-23 19:43:57		
<input type="checkbox"/>	+ ezadmin	root	centos server	input	Ended	0	2022-06-23 19:43:39		
<input type="checkbox"/>	+ ezadmin	root	centos server	output	Ended	0	2022-06-23 19:43:39		

1 - 6 / 6

Related Articles

[setup and configure ssh jump server](#)

[Upgrade Ezeelogin Jump server to the latest version](#)

[Restore ssh logs from the old Ezeelogin server to the new server](#)

Online URL:

<https://www.ezeelogin.com/kb/article/migrate-jump-server-installation-from-one-server-to-another-31.html>