Install Ezeelogin on SELINUX enabled Environment

319 Manu Chacko July 24, 2024 Installation, Technical 7815

How to install Ezeelogin on SELinux enabled environment?

Overview: This article helps Ezeelogin users to install Ezeelogin on an environment where SELinux is enabled.

Step 1: Whitelist all required services manually on SELinux. Check the allowed and blocked AVC by entering "**audit2allow -a**" command

```
[root@gateway ~]# audit2allow -a

#============== httpd_t ==============


allow httpd_t self:process ptrace;


#!!!! This avc can be allowed using one of the these booleans:

# httpd_can_network_connect, nis_enabled

allow httpd_t ssh_port_t:tcp_socket name_connect;
```

The output above from the **audit2allow -a** command indicates SELinux **denials** related to the **httpd_t (Apache HTTP Server) context.**

Step 2: As an example, run the below command to **allow** the blocked access of **httpd**

```
[root@gateway ~]# audit2allow -a -M httpd_t

[root@gateway ~]# semodule -i httpd_t.pp
```

The AVC for the **httpd** service will be allowed by entering the above commands. Similarly, allow all required services for Ezeelogin following the same example.

Check if there any services blocking on selinux like STEP 1 from the above example and Follow STEP 2 to allow it . Allow all by repeating the steps and ensure that there is no services blocking on SELINUX.

Contact ezeelogin support for any assistance **24*7 Live Chat** / **Ezeelogin support**

Related Articles:

Install Ezeelogin on older version of operating system

Install ezeelogin without internet access on Centos 7

Can i install ezeelogin Jump server solution in a lan?