Enforcing ssh login shell for ssh gateway users selectively in sshd_config file

336 admin July 25, 2024 Productivity & Efficiency Features, Security Features 9046

Enforce login shell for SSH users in the sshd configuration file.

<u>Overview</u>: This article describes how to enforce the ezsh shell for SSH users, excluding root, ted, and ben, in the sshd_config file, followed by restarting the SSH service.

• By default, the <u>Ezeelogin gateway users</u> are assigned the shell /usr/local/bin/ezsh however you may want the gateway users to have OS-level access (/bin/bash shell) when they log in via ssh.

This article describes how to enforce a specific shell for SSH users:

Step 1: Identify Current Shell:

• Determine the current shell assigned to the user by using the finger command.

```
root@jumpbox :~# finger ezadmin

Login: ezadmin Name:

Directory: /home/ezadmin Shell: /usr/local/bin/ezsh
```

Step 2: Modify sshd_config:

Edit the sshd configuration file (/etc/ssh/sshd config) on your gateway server:

• You can force every user into the /usr/local/bin/ezsh shell and exclude selected users by having the following parameters included in the /etc/ssh/sshd_config file of the gateway box. Append the following lines to the config file and restart the config file to apply the made changes.

```
root@jumpbox :~# /etc/ssh/sshd_config

Match User !root,!ted,!ben,?*
```

```
ForceCommand /usr/local/bin/ezsh
root@jumpbox :~# service sshd restart
```

• In the above eg., it would enforce <u>all the users</u> to default to the shell /usr/local/bin/ezsh on ssh login except for the user's root, ted, ben.

This would be the recommended way as it improves security by denying a /bin/bash shell for the SSH gateway users who do not need OS-level access on the gateway server and forcing them into the ezsh shell.

The users *root, ted, and ben* have been excluded hence would get OS-level access (/bin/bash shell on ssh login) and need to simply run the command *ezsh* to get the ezsh shell interface.

Adjust User Shell

To force the ezadmin user to the /bin/bash shell, run the following on the gateway box and exclude the user ezadmin in the /etc/ssh/sshd_config file only if ForceCommand parameters are in use.

root@jumpbox :~# chsh -s /bin/bash ezadmin.

Related Articles:

Run SSHD on different ports.

Changed settings when listening to a custom port.

Online URL:

https://www.ezeelogin.com/kb/article/enforcing-ssh-login-shell-for-ssh-gateway-users-selectively-in-sshd_config-file-336.html