
Clear two factor authentication

36 admin June 19, 2024 Two Factor Authentication (2FA) 10695

How to reset Google authenticator, DUO, Yubikey, Access keyword, Radius and FIDO2 two factor authentication (2FA) secrets for the gateway user?


Synopsis: This article will help Ezeelogin admin users to reset Google authenticator, DUO, Yubikey, Access keyword, Radius and FIDO2 two-factor authentication (2FA) secrets for the gateway user when the user is locked out or has forgotten their 2FA.



Prompt for 2FA when a user tries to log in to the GUI:




If the gateway user have admin privileges, they can click on the **reset password** icon, enable "Clear Two-Factor Authentication Secret," and then save the changes.



The gateway user can now log in without being asked for 2FA if 2FA is not enforced; otherwise, the user would be prompted to set up 2FA again.

How to reset Google Authenticator code individually?

Individual users can log into the GUI, navigate to **Account** -> **Google Authenticator** -> **Reset** to reset the Google Authenticator code.



Note: Emergency CLI Method

For Ezeelogin Version 7 and above:

1. To disable two-factor authentication (2FA) for the **admin user**, run the following commands.

```
root@jumpserver:~# php /usr/local/ezlogin/ez_queryrunner.php "update
prefix_settings SET value = 0 WHERE name = 'two_factor_auth'"
```

root@jumpserver:~# php /usr/local/ezlogin/ez_queryrunner.php "update
prefix_users set egs=NULL,eak=NULL,eyk=NULL,set_duo=0 where id=1"

2. To disable two factor authentication (2FA) for **all users**, run the following command.

root@jumpserver:~# php /usr/local/ezlogin/ez_queryrunner.php "update
prefix_users set egs=NULL,eak=NULL,eyk=NULL,set_duo=0"

Abbreviations:

```
eak = Access Keyword
eyk = Yubikey
egs = Google Authenticator
set_duo = DUO 2FA
```

Note: Emergency CLI Method

For Ezeelogin Version 6 and below:

Note:

User need to provide the correct db_name and dbprefix from ez.conf to run the MySQL commands manually.

1. Find database name and database prefix from /usr/local/etc/ezlogin/ez.conf from Ezeelogin gateway server.

```
root@jumpserver:~# cat /usr/local/etc/ezlogin/ez.conf | grep -i "db_name|db_user|db_pass|db_prefix"
```

db_name ezlogin_por

db_user ezlogin_cxy

db_pass ymhbtPaY)VzD2g]84

```
db_prefix casmbn_
2. Log in to MySQL command prompt
Note:
Replace the "db_user", "db_name" and "db_pass" with values in /usr/local/etc/ezlogin/ez.conf from the
Ezeelogin jump server.
root@jumpserver:~# mysql -u db_user -p db_name
3. Run the following command to clear the two-factor authentication (2FA) for the admin user.
Note:
Replace "dbprefix_" with the value of dbprefix_ from /usr/local/etc/ezlogin/ez.conf from the Ezeelogin
jump server.
Example: "dbprefix_settings" is to be replaced with "casmbn_settings".
mysql> UPDATE dbprefix_settings SET value = 0 WHERE name =
'two factor auth';
mysql> UPDATE dbprefix_users SET egs=NULL,eak=NULL,eyk=NULL,set_duo=0
where id=1;
4. Run the following command to clear the two-factor authentication (2FA) for all users.
mysql> UPDATE dbprefix users SET
egs=NULL,eak=NULL,eyk=NULL,set_duo=0;
```

Related Articles:

Enable/Disable 2FA [Two Factor Authentication] on Ezeelogir

How to enforce 2 Factor Authentication on user login'

How to disable 2FA from Ezeelogin GUI?

Disable two factor authentication from backend

Online URL: https://www.ezeelogin.com/kb/article/clear-two-factor-authentication-36.html