Access denied for user root by PAM account configuration

666 Rakhi April 18, 2025 Common Errors & Troubleshooting 6301

fatal: Access denied for user root by PAM account configuration [preauth]

Overview: This article explains how to fix the "Access denied for user root by PAM" error by disabling PAM in the SSH server configuration.

This error indicates issues with the PAM (Pluggable authentication module) configuration on your SSH server.

In the error log based on the distribution(O.S.) you are using; this would be the following error that you would receive.

```
root@gateway:~# tail -f /var/log/auth.log
Jan 6 05:21:56 gateway sshe[15778]: PAM adding faulty module: pam_pwdb.so
Jan 6 05:21:58 gateway sshe[15778]: Failed password for root from 192.168.0.108 port 56750 ssh2
Jan 6 05:21:58 gateway sshe[15778]: fatal: Access denied for user root by PAM account configuration [preauth]
Jan 6 05:22:06 gateway sshe[15781]: PAM unable to resolve symbol: pam_sm_acct_mgmt
Jan 6 05:22:06 gateway sshe[15781]: PAM unable to dlopen(pam_cracklib.so): /lib/security/pam_cracklib.so: cannot open shared object file: Not a directory
Jan 6 05:22:06 gateway sshe[15781]: PAM adding faulty module: pam_cracklib.so
Jan 6 05:22:06 gateway sshe[15781]: PAM adding faulty module: pam_bwdb.so: /lib/security/pam_pwdb.so: cannot open shared object file: Not a directory
Jan 6 05:22:06 gateway sshe[15781]: PAM adding faulty module: pam_pwdb.so
Jan 6 05:22:08 gateway sshe[15781]: Failed password for root from 192.168.0.108 port 56756 ssh2
Jan 6 05:22:08 gateway sshe[15781]: fatal: Access denied for user root by PAM account configuration [preauth]
```

You will not be able to log in to the remote server that has PAM misconfigurations. Following would be the error that would be received when you try to log in to the remote server that has existing PAM misconfigurations.

```
Enclountu 22

Enter a reason for accessing (4 to 100 characters): user_login

Oubuntu 22

Authentication by SSN key failed.
Authentication by password failed

Server: Oubuntu 22, port: 22

Press any key to continue...
```

This issue could be solved with the following steps where you would set UsePam to no in sshd conf file which means that the SSH server will not use the PAM for user authentication.

Run the following command and restart the sshd service:

```
root@gateway:~# sudo sed -i 's/^UsePAM .*/UsePAM no/' /etc/ssh/sshd_config root@gateway:~# systemctl restart sshd
```

And try to re-login to the remote server

Even if we've resolved the immediate issue by setting UsePAM to "no," consider revisiting the PAM configuration, verifying the paths and permissions of the modules mentioned in the error messages, and making the necessary corrections. This ensures that your system is configured securely while allowing for proper authentication.

For Reference: https://arlimus.github.io/articles/usepam/

Related Articles:

sshd[902]: debug1:PAM: password authentication failed for an illegal user: Authentication failure

sshd[3167]: pam_succeed_if(sshd:auth): requirement "uid >= 1000" not met by user "root"

Online URL:

https://www.ezeelogin.com/kb/article/access-denied-for-user-root-by-pam-account-configuration-666.html