

Disconnecting while logging into the remote server

683 Lekshmi April 23, 2025 [Common Errors & Troubleshooting](#) 1142

How to solve disconnection issues when attempting to log in to a server from the backend?

Overview: This article outlines how to resolve disconnection issues when logging in to a remote server from backend by verifying the logs and addressing issues related to duplicate entries.

Step 1: Tail the latest ezsh log of the user who attempted to log in to the server. Replace the username with the actual one.

```
root@gateway:~# tail -f /home/username/ezsh.log
```

OR

Tail [latest application log](#) and try to replicate the same error encountered earlier. Replace latest_log with the actual log filename.

```
root@gateway:~# tail -f /var/www/ezlogin/application/logs/latest_log
```

The example below illustrates how to diagnose and fix issues found in the SSH logs:

Step 2: If below error appears in the log, follow the steps outlined below to resolve the issue.

```
root@gateway:~# tail -f /home/linda/ezsh.log
New session started from 69.90.223.10:55130 to 10.10.8.21:22 on Wed
Feb 28 01:52:58 2024
Query failed (INSERT INTO `emhpp_sshlogs` (`user_id`, `server_id`,
`serveractivity_id`, `ssh_user`, `type`, `status`, `file`,
`encryption`, `mexecid`, `created`) VALUES ('49', '2728', '0',
'root', 'input', 'begin', '/var/log/ezlogin/input/linda/root~cwh27.ad
mod.com~Wed_Feb_28_01:53:19_2024', '1', '', NOW())): Error 1062:
Duplicate entry '1248166' for key 'PRIMARY'
SSH log entry (/var/log/ezlogin/input/linda/root~admod.com~Wed_Feb_28
_01:53:19_2024) creation failed: 0
```

Step 2(A): Identify the duplicate entry in the table mentioned in the ezsh.log and log into MySQL. In this case, the duplicate entry identified by its primary key is 124866.

Step 2(B): Modify the INSERT query to include a new column called 'id', and assign it a value

that is one higher than the duplicate entry shown in the ezsh.log. Make sure to replace the values for **id**, **user_id**, **server_id**, **serveractivity_id**, **ssh_user**, **type**, **status**, **file**, **encryption**, **mexecid**, and **created** with the actual values specific to your case.

```
mysql> INSERT INTO `emhpp_sshlogs` ( `id`, `user_id`, `server_id`, `serveractivity_id`, `ssh_user`,  
`type`, `status`, `file`, `encryption`, `mexecid`, `created`) VALUES ('1248167', '49', '2728', '0', 'root',  
'input', 'begin', 'path_to_file', '1', '', NOW());
```

Step 2(C): Delete the previously created entry from the table using a DELETE query. Replace "table_name" and "value" with the correct values. This will set the increment value correctly.

```
mysql> delete from table_name where id= value;
```

Example:

```
mysql> delete from emhpp_sshlogs where id= 1248167;
```

Step 3: Once done, try logging in again to the server that previously failed during the login attempt.

For a permanent solution, the best option would be to take a database dump and then re-import it, or alternatively, [update](#) the currently used Ezeelogin to the same version.

Related Articles:

[Upgrade Ezeelogin Jump server to the latest version](#)

[Basic MySQL commands for troubleshooting database related issues in Ezeelogin](#)

Online URL:

<https://www.ezeelogin.com/kb/article/disconnecting-while-logging-into-the-remote-server-683.html>